# LIGHT METER (ECONOMIC TYPE)
# CODE 0131-A120

VIDEO




- Photosensor can rotate 90° clockwise and 180° counterclockwise
- Build-in calibration filters ensure the accuracy when working in different colors
- Data hold function
- Lux/FC unit switch
- Low battery alarm

## SPECIFICATION

| | | | | |
|---|---|---|---|---|
| **Measuring range** | 0.1~199.9Lux | 1~1999Lux | 10~19990Lux | 100~199900Lux |
| **Resolution** | 0.1Lux | 1Lux | 10Lux | 100Lux |
| **Measuring range** | 0.01~19.99FC | 0.1~199.9FC | 1~1999FC | 10~19990FC |
| **Resolution** | 0.01FC | 0.1FC | 1FC | 10FC |
| **Accuracy** | ±(4%+10d), range<20000Lux/2000FC<br>±(5%+10d), range≥20000Lux/2000FC<br>(d is resolution, calibrated with standard incandescent lamp at color temperature 2856K) | | | |
| **Repeatability** | ±2% | | | |
| **Sampling time** | 0.5s | | | |
| **Operation environment** | 0~40°C, 0~70%RH | | | |
| **Storage environment** | -10~50°C, 0~80%RH | | | |
| **Power supply** | 9V battery | | | |
| **Dimension** | 185×68×38mm | | | |
| **Weight** | 130g | | | |

## STANDARD DELIVERY

| | |
|---|---|
| **Main unit** | 1 pc |
| **Battery** | 1 pc |

## OPTIONAL ACCESSORY

| | |
|---|---|
| **Tripod** | **0701-TR175** |