THERMOCOUPLE THERMOMETERS (STANDARD TYPE)

IP52 WATERPROOF

VIDEO

- Unit: °C/°F
- Support thermocouple type K/J/T
- MAX/MIN/AVG mode
- Temperature upper and lower limit alarm function
- Graphical display
- Multi-point calibration function
- Display backlight
- Data hold function
- Battery level display
- Automatic power off



0326-CT31

SPECIFICATION

Code		0326-CT31	0326-CT32
Channel number		1	2
Weight		233g	248g
Thermocouple type		K/J/T	
Temperature range	type K	-200°C~1370°C	
	type J	-200°C~1200°C	
	type T	-200°C~400°C	
Temperature accuracy*		±(0.3%·|t|+0.40)°C	
Temperature resolution		0.01°C	
Sampling rate		2 times/sec	
Display		dot matrix LCD display with backlight	
Operation temperature		-10°C~+50°C (non-condensing)	
Storage temperature		-20°C~+60°C (without battery)	
Power supply		3×AAA alkaline batteries	
Dimension		174×73×40mm	

*Temperature accuracy does not include thermocouple error

SPECIFICATION OF K-TYPE THERMOCOUPLE *

Code	Range	Accuracy	Length
0326-K01	-40°C~300°C	±1.5°C	1.5m

*Other types, temperature range and length of thermocouples can be customized

STANDARD DELIVERY

Main unit	1 pc
Battery (AAA)	3 pcs
K-type thermocouple (0326-K01)*	1/2 pcs

*Number of thermocouples is corresponding to the number of channels