# DC POWER SUPPLY (BASIC TYPE)
# CODE 9911-PS305

## STANDARD DELIVERY

| | |
|---|---|
| Main unit | 1 pc |
| Test lead | 2 pcs |


## SPECIFICATION

| | | |
|---|---|---|
| Voltage | range | 30V |
| | setting resolution | 10mV |
| | setting accuracy | ≤0.1%+20mV |
| | readback resolution | 10mV |
| | readback accuracy | ≤0.1%+20mV |
| | load regulation | ≤0.1%+5mV |
| | line regulation | ≤0.01%+5mV |
| | ripple | 10mVrms |
| Current | range | 5A |
| | setting resolution | 1mA |
| | setting accuracy | ≤0.2%+6mA |
| | readback resolution | 1mA |
| | readback accuracy | ≤0.2%+6mA |
| | load regulation | ≤0.2%+3mA |
| | line regulation | ≤0.2%+3mA |
| | ripple | 8mArms |
| OVP | | 0~33V |
| OCP | | 0~5.5A |
| Work condition | | temperature: 0~40°C, humidity: ≤80%RH |
| Storage condition | | temperature: -20~60°C, humidity: ≤80%RH |
| Cool system | | fan cool |
| Power supply | | AC 220V±10%, 50Hz/60Hz |
| Dimension (L×W×H) | | 230×80×150mm |
| Weight | | 1.45kg |




VIDEO

- Four-digit LED display
- Output power display
- Output switch control
- Panel locking function to prevent misoperation
- USB interface for power supply
- OVP/OCP protection
- 3 shortcut keys for presetting



test leads (included)