# IMPACT SPECIMEN NOTCH PROJECTORS

CAN BE CUSTOMIZED

VIDEO

- Suitable for inspecting the notching quality of impact specimens of Charpy V-notch (depth of 2mm) and U-notch (depth of 2mm)
- Standard sample drawings with tolerances, angle values and depth lines on the screen for intuitive and efficient comparison




ISP-Z1

**SPECIFICATION**

| Code | ISP-Z1 | ISP-Z2 |
|---|---|---|
| Corresponding standard | GB/T 229 | GB/T 229, ASTM E23, ISO 148, ISO 83, EN 10045 |
| Magnification | 50X | |
| Magnification of lens | 2.5X | |
| Magnification of projector lens | 20X | |
| Diameter of projector screen | Ø200mm | |
| Size of square stage | 110×125mm | |
| Size of round stage | Ø90mm | |
| Diameter of glass on stage | Ø70mm | |
| Stroke of stage (X axis) | ±10mm | |
| Stroke of stage (Y axis) | ±10mm | |
| Stroke of stage (Z axis) | ±12mm | |
| Range of stage rotation | 0°~360° | |
| Illumination (tungsten halogen lamp) | 12V 100W | |
| Power supply | AC 220V, 50Hz 150W | |
| Dimension (L×W×H) | 510×220×600mm | |
| Weight | 20kg | |

**STANDARD DELIVERY**

| | |
|---|---|
| Main unit | 1 pc |