HOT MOUNTING RESIN



- Suitable for small sample preparation

Code	Color	Description	Package
MLP-DR1	black	1. for common sample preparation, fast grinding speed 2. usage: 135±5°C, 5~8min	0.5kg
MLP-DR2			1kg
MLP-DR3			4kg
MLP-DR4	black	1. edge protection type, sample binding, high hardness, slow grinding speed 2. usage: 140±5°C, 8~15min	0.5kg
MLP-DR5			1kg
MLP-DR6			4kg
MLP-DR7	black	1. carbon phenolic polymer, high electrical conductivity, used in fields such as SEM and TEM 2. usage: 140±5°C, 8~15min	0.5kg
MLP-DR8			1kg
MLP-DR9	red	1. for common sample preparation, fast grinding speed 2. usage: 135±5°C, 5~8min	0.5kg
MLP-DR10			1kg
MLP-DR11	white	1. for common sample preparation, fast grinding speed 2. usage: 135±5°C, 5~8min	0.5kg
MLP-DR12			1kg
MLP-DR13			4kg
MLP-DR14	green	1. for common sample preparation, fast grinding speed 2. usage: 135±5°C, 5~8min	0.5kg
MLP-DR15			1kg
MLP-DR16			4kg
MLP-DR17	transparent	1. transparent, soluble, for sample with size, position, depth and other requirements 2. usage: 150±5°C, 15~20min	0.5kg
MLP-DR18			1kg
MLP-DR19			4kg